



KEY

- Cone
- Sign
- Work area
- ⬇ Traffic light head
- ⬇ Traffic light phase

DETAIL B

Single dual carriageway 40m or less - 450mm traffic cones, spacing 1.5m.  
Single dual carriageway 50m or more - 750mm traffic cones, spacing 1.5m.  
Dual carriageway / national speed limit - 750mm traffic cones, spacing 1.5m.  
No warning sign.

Notifying darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2/45 degree tapes than 1.5m spacing and no relaxation.  
1/2 degree tapes than 1.5m spacing and no relaxation.  
Cone will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40m or less - 450mm traffic cones.  
Single dual carriageway 50m or more - 750mm traffic cones.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Min width of sideways safety zone (S)	0.5 m
Min length of longways clearance (L)	0.5m
Speed of the road	30

Rev	Description	Revisions	By	Chk	Date

Client:

XEIAD

Project:  
Station road, Worcester WR6 5JH

Title:

FULL ROAD CLOSURE

SAFER  
ROADWORKS

DESIGN: DTM	DRAWN: LC	CHECK: PB
DATE: 08.10.24	DATE: 08.10.24	DATE: 08.10.24
SCALE: AS NTS	STATUS: Proposed	
Drawing No	SRW/LC	Rev: 1